



SPECS

Hot Water Pressure Washers

ELECTRIC MODELS 1600-2V # N83901

2000-3V # N83801

2000-4V # 825701

3200-4V # N83701



SPECIFICATIONS

	1600-2V	2000-3V	2000-4V	3200-4V
Pressure	1600 PSI	2000 PSI	2000 PSI	3200 PSI
Flow Rate	2.0 GPM	3.0 GPM	3.8 GPM	3.6 GPM
Motor Horsepower	2.3 HP	4.0 HP	5.0 HP	8.0 HP
Voltage	115V	230V	230V	230V
Phase	1 PH	1 PH	1 PH	1 PH
Current (Amps)	20 amps	20 amps	25 amps	36 amps
Burner Type	Vertical – Oil Fired	Vertical – Oil Fired	Vertical – Oil Fired	Vertical – Oil Fired
High Temp. Cut-Off	225° High Limit	225° High Limit	225° High Limit	225° High Limit
Safety Relief Valve	Standard	Standard	Standard	Standard
Drive System	Belt	Belt	Belt	Belt
Soap Control	¼” metering valve (upstream injection)	¼” metering valve (upstream injection)	¼” metering valve (upstream injection)	¼” metering valve (upstream injection)
Gun Type	Trigger Control	Trigger Control	Trigger Control	Trigger Control
Hose	3/8” x 50’	3/8” x 50’	3/8” x 50’	3/8” x 50’
Frame / Carriage	4 wheel portable	4 wheel portable	4 wheel portable	4 wheel portable
Size (L x W X H)	43” x 27” x 39”	43” x 27” x 39”	43” x 27” x 40”	43” x 27” x 40”
Weight	420 lbs.	420 lbs.	545 lbs.	730 lbs.

AVAILABLE ACCESSORIES

- Manual Hose Reel
- Adjustable Time Delay Shutdown
- Non-marking extension hose w/ quick disconnects 3/8” x 50’
- Steam Combustion Kit
- Rotary Nozzle
- Hour Meter
- Downstream Chemical Injector