



DYNA-CLEAN PARTS WASHER

#915201 Dyna-Clean Basin and Drum

#915301 Dyna-Clean Basin only

FEATURES

- All-steel construction
- Powder coat paint finish
- Tool-less assembly
- Spring-loaded lid for easy opening and closing
- 168 gph UL/CSA approved submersible electric pump which operates on 115 volt, 1 amp
- Model 5100 filtration system with 50-micron polypropylene particulate filter with visible filter bowl
- Filter change indicator signals when the 5100 filter needs to be changed
- 165°F UL approved fire link. In the unlikely event of a fire, the link separates, permitting the lid to close – containing the fire
- Directional spout with on/off control
- Convenient tool rack

SPECIFICATIONS

Tank Size:	32" x 22" x 10"
Tank Capacity:	30 gallons
Overall Size:	32" x 22" x 40"
Weight:	122 lbs. with drum

SAFETY EQUIPMENT

892101	Nitrile Elbow Length Gloves, Size 9
892201	Nitrile Elbow Length Gloves, Size 10
770201	Spectra-Clear Safety Gloves
925501	Wilson Sport Safety Glasses
942301	Safety Faceshield
942601	Safety Polyethylene Cap

PRODUCTS TO USE

0366	Zep Dyna 143°
0179	Zep Dyna 170°
0369	Dyna Blue
F015	Dyna 680T2



The Zep Dyna-Clean is the standard by which most solvent-based parts washers are measured. Designed for fast, efficient and economical cleaning of dirty or greasy parts.

Zep's exclusive filtration system extends solvent life and helps protect the environment. Instead of large volumes of potentially-hazardous fluid hauled off from the work-site, only the filter elements are disposed of. The Zep Model 5100 filter can remove particles down to 10 microns (with optional element). The Dyna-Trap filter bag removes oils and greases – extending solvent life. Convenient Filter Change Indicator lets you know when it's time for a new filter.

FEATURES

STANDARD



SPRING-LOADED, FIRE-PROTECTIVE SAFETY LID utilizes a fusible link that melts at 160° to close the lid automatically in the event of a fire.



FLEXIBLE 24" PLASTIC SPOUT delivers solvent into the wash tank. The spout bends easily to allow access to hard-to-reach spots on parts.



REMOVABLE PLASTIC SINK STRAINER provides drainage and prevents large particles from falling into the solvent drum. When soaking parts use the **MAGNETIC DRAIN STOPPER** to maintain solvent level in the tank.



SUBMERSIBLE, CENTRIFUGAL PUMP is a rugged UL approved pump. Fittings and hoses are designed for years of trouble-free service.



Remove stubborn debris from parts with the **PARTS WASHING BRUSH**. When not in use, the brush can be stored on the lid.



DYNA TRAP FILTER SPOUT provides a convenient hook-up for operation of the Dyna Trap Filter Bag.



CONTROLS are conveniently located on the unit for easy access. Toggle switches operate the solvent pump. All wiring is 115 volt, corrosion resistant and three-wire safety grounded.



MODEL 5100 FILTER SYSTEM is mounted below the tank to allow easy access when the filter has to be replaced. The translucent styrene canister has an aluminum head.

FILTERS

- 904902** Replacement 5110 (10 micron) particulate filter element (box of two)
- 905502** Replacement 5150 (50 micron) particulate filter element (box of two)
- 900402** Replacement 5199 (100 micron) particulate filter element (box of two)
- 903402** Dyna-Trap filter bag (box of two)
- 916401** Dyna-Trap cover
- 916501** Dyna-Clean new work platform
- 907101** Dyna-Clean filter pad - new
- F77201** Dyna Blue Bowl



WORK PLATFORM



DYNA TRAP FILTER

ACCESSORIES

- 903501** Oriflo "Flow-Thru" Cleaning Brush
- 903001** 30 gallon Open Head Steel Drum
- 903701** Foot pedal switch
- 903901** Parts basket- 21.5" x 10.5" x 7.75"
- 906301** Work light